

Ground Support Equipment

CT-03 CARGO DOLLY 10 FT. (Finger Dolly)

Dimensions

Maximum length	4.566 mm
Maximum width	3.415 mm
Tara Weight	1.220 kg
Max load	6.800 kg
Suitable for	LD1, LD3, LD4, LD6, LD7, LD8, LD9, LD11, LD29, MH1, PKC, FQA, PBJ, PAG, PMC



Specification

Finish	Hot dip galvanised
Turntable deck	No
Type of rollers	Cargo rollers Ø89 mm, bolted
Tow-Bar	1.555 mm
Tow-Eye diameter	Ø40 mm
Parking brake	On front wheels, activated when in upwards position
Type of steering	Ackerman steering, 2 wheel steering
Tyres	8
Wheel type (dia)	3.00 D / 15 x 4.5 - 8
Maximum speed (unloaded)	25 km/h
Type of loading	Narrow Edge Loading
Coupling	S-P-S E-Hitch

Options

Coupling	Ringfeder, Rockinger
----------	----------------------

The specified dimensions and weight are indicative and no rights can be derived from this publication.

S-P-S International • Toekanweg 2 • 1118 EB Schiphol, The Netherlands

Phone: +31 20 354 00 63 • sales@s-p-s.aero • www.s-p-s.aero