



# Ground Support Equipment

## CT-08 CARGO DOLLY 10 FT.

#### **Dimensions**

Maximum length	5.080 mm	Å
Maximum width	2.707 mm	A CONTRACT
Tara Weight	1.235 kg	The second second
Max load	6.800 kg	The second se
Suitable for	LD1, LD2, LD3, LD5, LD6, LD9, LD10, LD11, P1, P6, P9	

#### **Specification**

Finish	Hot dip galvanised
Turntable deck	No
Type of rollers	Cargo rollers Ø89 mm, bolted
Tow-Bar	1.448 mm
Tow-Eye diameter	Ø40 mm
Parking brake	On front wheels, activated when in upwards position
Type of steering	Turntable steering, 2 wheel steering
Tyres	8
Wheel type (dia)	3.00 D / 15 x 4.5 - 8
Maximum speed (unloaded)	25 km/h
Type of loading	Wide Edge Loading
Coupling	S-P-S E-Hitch

### **Options**

Coupling

Ringfeder, Rockinger

The specified dimensions and weight are indicative and no rights can be derived from this publication. S-P-S International • Toekanweg 2 • 1118 EB Schiphol, The Netherlands Phone: +31 20 354 00 63 • sales@s-p-s.aero • www.s-p-s.aero