

Ground Support Equipment

CT-16_1 10FT CARGO DOLLY

Dimensions

| | |
|----------------|---|
| Maximum length | 5.376 mm |
| Maximum width | 2.656 mm |
| Tara Weight | 1.335 kg |
| Max load | 6.800 kg |
| Suitable for | PEA, PEB, PYB, PJB, PBM, PAG, PAJ, PME, PRA, AAA, AAC, AAY, AAK, AAJ, ALP, AAZ, AAX, AMJ, AMD, ABU, AMX, AXY, AKE, DPM, DQF |



Specification

| | |
|--------------------------|---|
| Finish | Hot dip galvanised |
| Turntable deck | No |
| Type of rollers | Castor rollers |
| Tow-Bar | 1.604 mm |
| Tow-Eye diameter | Ø40 mm |
| Parking brake | On front wheels, activated when in upright position |
| Type of steering | Turntable steering , 2 wheel steering |
| Tyres | 8 |
| Wheel type (dia) | 3.00 D / 15 x 4,5 - 8 |
| Maximum speed (unloaded) | 25 km/h |
| Type of loading | Wide Edge Loading |
| Coupling | S-P-S E-Hitch |

Options

| | |
|----------|----------------------|
| Coupling | Ringfeder, Rockinger |
|----------|----------------------|